JANDON™
Useful Everyday

Model #5103C-WS

Single-Handle Kitchen Faucet with Side Spray
Fits 4 Hole Sink, 6" or 8" Centerset

+ Helpful Information

Helpful Tools

Tools:

Gather the neccessary tools as shown below to complete the installation of this faucet. Some may not be needed depending on the model of faucet you are installing. Check with you local hardware store on the requirements of your installation.



1 Spray Hole Installation



A. Insert spray hose assembly (1) to far right hole on sink. Hand tighten with nut from underneath.

B. Place mount screw (8) on outer holes for 8" and inner holes for 6" installation.

C. Connect male end (3) with spray and hand tighten.

2 Assembly



A. Clean installation site, removing any debris from the area.

B. Remove mounting nut (4) and clamp bar (5) while keeping deck gasket (10) attached.

C. Place mount screw (8) on outer holes for 8" and inner holes for 6" installation.

D. Pull spray hose (6) through sink center hole and connect with faucet diverter (9).

3 Mounting



A. Place faucet onto sink, replace clamp bars then attached mount nut and tighten.

4 Water Supply Lines



Connect to water supply lines with either:
(A) 3/8" O.D. copper tubing (ball nose risers with the coupling nuts)
(B) copper tubing (no ball) with supplied tube head interior connector or)
(C) IPS faucet connectors (1/2").

Important:
Tighten connection with two wrench to prevent damage to tube body.
Bending of stem will void warranty.

Important:
Remove the aerator and let both hot and cold water run for one minute. This will help clean any debris that might otherwise clog the system. Replace aerator.

Test system for leak

5 Parts List



No.	parts #	Pattern name
39	ZU-0011-10	Base Assembly
38	ZU-0011-09	Lock Nut
37	ZU-0011-08	Handlebase
36	ZU-0011-07	Press Ring
35	ZU-0011-06	Diverter
34	ZU-0011-05	Diverter Seat
33	ZU-0011-04	Diverter Body
32	ZU-0011-03	Diverter Seat
31	ZU-0011-02	Diverter Cap
30	ZU-0011-01	Aerator Outlet
29	ZU-0010-14	Aerator Body
28	ZU-0010-13	Aerator Bolt
27	ZU-0010-12	Screening Bracket
26	ZU-0010-11	Aerator Cap
25	ZU-0010-10	Screen Net
24	ZU-0010-09	Screen Cap
23	ZU-0010-08	Screening Bracket
22	ZU-0010-07	Handle Base
21	ZU-0010-06	Handle Cap
20	ZU-0010-05	Screw Cap
19	ZU-0010-04	Screw
18	ZU-0010-03	Screening Bracket
17	ZU-0010-02	Handle Base
16	ZU-0010-01	Handle Cap
15	ZU-0007-08	Screw
14	ZU-0007-07	O-Ring
13	ZU-0006-01	Tube
12	ZU-0005-01	Flip Stop
11	ZU-0004-01	Connector
10	ZU-0003-01	Connector
9	ZU-0002-01	Tube
8	ZU-0001-01	Up Stop Screening Ring
7	ZU-0000-01	Screw Bracket
6	ZU-0000-02	Set Screw
5	ZU-0000-03	Screw Bracket
4	ZU-0000-04	Screw
3	ZU-0000-05	Screw
2	ZU-0000-06	Screw
1	ZU-0000-07	Screw

6 Maintenance and Care

Question:
What is the best method of cleaning the faucet?

Answer:
The best way to clean the faucet is to use a clean damp cloth without any chemical cleaning agents. All Jandon Faucet are manufactured using quality coating technique and should make the finish last for a very long time without corrosion.

Question:
How do you clean the faucet cartridge?

Answer:
To clean the cartridge first you will need to shut off the water supply. Remove the handle(s) and then the cartridge. Flush the cartridge with water and then soak for five minutes. Replace parts in reverse order.

7 Troubleshooting

Question:
My newly installed faucet drips after I shut it off.

Answer:
Operate the handle on and off about 15-20 times. This will remove any air left in your supply lines.

Question:
The tailpiece that came with my lavatory faucet is not long enough.

Answer:
Depending on the distance of your sink setup you may need to purchase a longer tailpiece available at any hardware store.

Question:
What is ceramic disc valving?

Answer:
Ceramic disc valves are the latest in valve design. They control the water flow by using two airtight disc that glides back and forth. The materials of the ceramic disc are as hard as diamonds. Hence they are unaffected by temperature extremes, sand, rust or hard water conditions. With these performance parts, Jandon Faucet guarantees a drip-free and maintenance-free performance.

? Troubleshooting

Question:
Why is water pressure low or improper water pattern?

Answer:
Make sure water supply valve is fully opened. Low pressure and improper water pattern could be caused by debris inside the aerator. Remove aerator by gently turning counter-clockwise, and then flush inside the aerator to clear away any debris. Install back and test.

Question:
Why is the handle lose?

Answer:
Your faucet's handle are designed to be interchangeable. Sometimes the handle might get lose if the set screw is not tighten inward enough. Use the included hex wrench to tighten.

Question:
Why is water leaking beneath the sink?

Answer:
Make sure the upper gasket of the pop up is properly seated. Also you might want to further tighten the nut from underneath. Furthermore, the use of silicon or putty might help gaps seal better.

Additional Help information:
For additional product information or assistance you may contact us online.
Website http://www.jandonfaucet.com
Email: info@jandonfaucet.com

! Warranty Information

Jandon Faucet warrants the original purchaser (must have prove of purchase) that such product is free from defect in materials or workmanship for a period of ten years for non-commercial use and two years for commercial use, from date of purchase. To obtain warranty services please call 1-888-526-3688 to receive RMA # for the merchandise return. This warranty is limited to but not including labor charges incurred and/or damages sustained during installation, repair or replacement, nor incidental or consequential damages. This warranty does not cover items which have received secondary finishing or have been altered or modified after purchase, or for defects caused by physical abuse to or misuse of the product. This warranty gives the original purchaser of a Jandon Faucet specific legal rights which may vary from state to state or from province to province. In some states or provinces the exclusion or limitation of incidental or consequential damages is not allowed, so those exclusions may not apply to you.

Thank you for your purchase.
Please use only genuine JANDON replacement parts

JANDON™
Useful Everyday

Jandon Faucet Corporation
Toll Free: 1-877-526-3688 Fax: 1-718-326-8124
Visit us online @ www.jandonfaucet.com