JANDON FAUCET™

Useful Everyday

Model #6240C

Two Handle Kitchen Faucet
Single Hole Installation

+ Helpful Information

Helpful Tools

Tools: .....

Shown below are tools that may be required to comlete the installation. They are not included, however you could easily purchase them at any hardware store. When choosing you installation supplies, make sure they are UL tested.

Maintenance:.....

Simply rinse the surface with clear water or mild liquid detergents (if necessary). Dry the faucet with a clean soft cotton cloth. Do not use any cleaning agents containing acids, polish abrasives, or harsh cleaners.

Additional Help information:.....

For additional product information or assitance you may contact us online.
Website http://www.jandonfaucet.com
Email: info@jandonfaucet.com

1 Faucet Installation



A. Shut off water supply and drain lines. Clean sink surface throughly. Make sure mounting area is clean and dry.

B. Remove clamp nut (3), clamp (2) and clamp gasket (1).

C. Place faucet in place on sink deck, check alignment.

2 Faucet Installation



A. From underneath the deck, place clamp gasket (1), clamp (2) and nut (3) onto mount screw (4). They should be position so that both water inlet holes are exposed.

B. Screw on male end (5) of inlet hoses and tighten.

C. Connect female end (6) of hoses to water supply.

D. Check system for leaks.

3 Parts Diagram / List



No.	Part #	Part Name
1	JD-8005-01	Body
2	JD-8801-02	O-Ring
3	JD-8821-06	Ceramic Cartridges
4	JD-8803A-15	Spout Nut
5	JD-8803A-11	O-Ring
6	JD-8821-05	Cap W/Adjusting Ring
7	JD-8821-04	Handle
8	JD-8801-05	Handle Screw
9	JD-8821-03	Handle Nut
10	JD-8821-02	Button (Hot)
11	JD-8803A-12	Retaining Ring
12	JD-8803A-13	Spout Adapter
13	JD-8803A-14	O-Ring
14	JD-8801-12	Aerator Assembly
15	JD-8801-13	Aerator Gasket
16	JD-8825-01	Spout
17	JD-8821-08	Button (Cold)
18	JD-8801-08	Hose Assembly
19	JD-8801-09	Hardwear package
20	JD-8805-03	Gasket

4 Maintenance and Care

Question:
What is the best method of cleaning the faucet?

Answer:
The best way to clean the faucet is to use a clean damp cloth without any chemical cleaning agents. All Jandon Faucet are manufactured using quality coating technique and should make the finish last for a very long time without corrosion.

Question:
How do you clean the faucet cartridge?

Answer:
To clean the cartridge first you will need to shut off the water supply. Remove the handle(s) and then the cartridge. Flush the cartridge with water and then soak for five minutes. Replace parts in reverse order.

5 Troubleshooting

Question:
My newly installed faucet drips after I shut it off.

Answer:
Operate the handle on and off about 15-20 times. This will remove any air left in your supply lines.

Question:
The tailpiece that came with my lavatory faucet is not long enough.

Answer:
Depending on the distance of your sink setup you may need to purchase a longer tailpiece available at any hardware store.

Question:
What is ceramic disc valving?

Answer:
Ceramic disc valves are the latest in valve design. They control the water flow by using two straight disc that glides back and forth. The materials of the ceramic disc are as hard as diamonds. Hence they are unaffected by temperature extremes, sand, rust or hard water conditions. With these performance parts, Jandon Faucet guarantees a drip-free and maintenance-free performance.

? Troubleshooter

Question:
Why is water pressure low or improper water pattern?

Answer:
Make sure water supply valve is fully opened. Low pressure and improper water pattern could be caused by debris inside the aerator. Remove aerator by gently turning counter-clockwise, and then flush inside the aerator to clear away any debris. Install back and test.

Question:
Why is the handle lose?

Answer:
Your faucet's handle are designed to be interchangeable. Sometimes the handle might get lose if the set screw is not tighten inward enough. Use the included hex wrench to tighten.

Question:
Why is water leaking beneath the sink?

Answer:
Make sure the upper gasket of the pop up is properly seated. Also you might want to further tighten the nut underneath. Furthermore, the use of silicon or putty might help gaps seal better.

! Warranty Information

Jandon Faucet warrants the original purchase (must have prove of purchase) that such product is free from defect in materials or workmanship for a period of ten years for non-commercial use and two years for commercial use, from the date of purchase. To obtain warranty services please call 1-877-526-3668 to receive RMA# for the merchandise return. This warranty is limited to but not including labor charges incurred and/or damages sustained during installation, repair or replacement, nor incidental or consequential damages. This warranty does not cover items which have received secondary finishing or have been altered or modified after purchase, or for defects caused by physical abuse to or misuse of the product. This warranty gives the original purchaser of a Jandon Faucet specific legal rights which may vary from state to state or from province to province. In some states or provinces the exclusion or limitation of incidental or consequential damages is not allowed, so those exclusions may not apply to you.

Thank you for your purchase!

JANDON™ Useful Everyday
Jandon Faucet Corporation
Toll Free: 1-877-526-3668 Fax: 1-718-326-8124
Visit us online @ www.jandonfaucet.com